

### Special Features

- ▲ FACTORY ASSEMBLED FOR EASY, LOW COST INSTALLATION
- ▲ SPACE SAVING DESIGN
- ▲ INDIVIDUAL TIMED FLOW VALVES FOR WATER ECONOMY
- ▲ GRADE 316 STAINLESS STEEL CONSTRUCTION

### Description

The product is specifically designed for installing near to beaches or swimming pools, providing bathers with showering facilities. The beach shower is free standing and is factory assembled with either two, three or four individual timed flow water control outlets which are pre-piped requiring only a single supply connection.

### Construction

The beach shower is constructed from heavy gauge grade 316 stainless steel, with all exposed surfaces polished to a satin finish. Incorporated in the shower column is a heavy duty base mounting flange and a removable access panel held in position by security type screws. The shower is supplied factory fitted with a fixed spray head and timed flow push button valve for each user together with a water supply manifold and all internal piping. Models are available to suit 2, 3, or 4 users. A steel anchor plate, coated with a rust preventative, together with reinforcing bars provides a secure mounting for the shower.

### Operation

Each user has their own fixed spray head and push button timed flow valve which is adjustable to give between 5 and 60 seconds operation. The beach shower is designed to connect to a single pipe, from below supplying either cold or temperature controlled warm water. If the installation is subject to freezing then the installer should provide a water drain down facility.



## Technical Specification: Beach Shower

5 Brearley Court, Baird Road, Waterwells Business Park, Quedgeley, Gloucester GL2 2AF Tel: 01452 721211 Fax: 01452 721231 Web: www.acornpowell.co.uk

### Number of Users

The beach shower is available to suit either 2, 3, or 4 users.

### Spray head, Shower valve and Fittings

The beach shower is supplied, as standard, with the following:

Fixed vandal resistant spray head (one per user).

Push button timed flow valve adjustable to give between 5 and 60 seconds operation (one per user). Valve factory set at approximately 10 seconds.

Water supply manifold with single supply inlet of 19 mm (¾ in) diameter copper pipe.

Steel anchor plate with rust preventative coating and reinforcing bars.

### Water Supply and Pressure

A cold or temperature controlled water supply is required for the beach shower. The supply pipework should be a minimum of 28 mm diameter reducing in size within the column. For satisfactory operation a minimum water pressure of 1.2 bar g. is required at the point where the supply enters the column. For water pressures in excess of 8.0 bar g. a flow control or pressure reducing valve must be fitted. If the installation is subject to freezing then the installer should provide a water drain down facility.

### Product Code Selection for Order or Quotation

#### 1. Base Product Code

621-beach shower

#### 2. Number of Users

-2

-3

-4

